



Art No. WL0084B

Wireless N 150Mbps USB Adapter Ultra-Nano Size

Feature:


- Chipset: Ralink RT5370
- Ultra-Nano size design
- Complies with IEEE802.11b/g/n standards
- High transfer data rate up to 150Mbps
- Supports 64/128-bit WEP, WPA, WPA2, WPA-PSK and WPA2-PSK Encryption
- Supports WiFi Protection Setup (WPS)
- Supports USB 2.0/1.1 interface
- Supports Windows 2000/XP/Vista/7/8, Linux 2.6.x and MAC OS

Package Contents:

- 1 x Wireless N USB Adapter
- 1 x Quick Installation Guide
- 1 x CD (Driver + Utility + Manual)
- 1 x Protector Cap

Packaging Information:

- Packing Dimension: 100x164x25mm
- Packing Weight: 0.05kg
- Carton Dimension: 427x337x362 mm
- Carton Q'ty: 240pcs
- Carton Weight: 12.1kgs





* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.





Art No. WL0084B

Wireless N 150Mbps USB Adapter Ultra-Nano Size

Specification:

Chipset Solution	Ralink RT5370
Standard	IEEE 802.11b/g/n, 1T1R mode
Interface Type	USB 2.0 /1.1
Frequency Band	2.4000~2.4835GHz (Industrial Scientific Medical Band)
Data Rate	For 802.11b/g: Peak rate 54Mbps, Peak throughput: 27Mbps
	For 802.11n: Peak rate: 150Mbps, Peak throughput: 90Mbps
Transmit Power	802.11b: 18dBm; 802.11g: 15dBm; 802.11n: 13dBm
Power	5V DC input, 130mA
Consumption	
Transmission	Indoor up to 100m, outdoor up to 300m (Standard transmission
Distance	distance, it is affected depending on different environment).
Security	64/128-bit WEP, WPA, WPA2, WPA-PSK and WPA2-PSK Encryption
	WiFi Protection Setup (WPS)
Supported OS	Windows 2000/XP/Vista/7/8, Linux 2.6.x and MAC OS
Dimension	6(H) x 13.5(W) x 23(D) mm
Temperature	Operating Temperature: 0°C~40°C
	Storage Temperature: -20~60°C
Humidity	Operating Humidity: 10%~85% non-condensing
	Storage Humidity: 5%~95% non-condensing





* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.